



# Shandong Chik Bearing Co., Ltd.



R14ZZ Bearing 2D drawings and 3D CAD models

22,225 mm x 47,625 mm x 12,700 mm NTN  
R14ZZ deep groove ball bearings

Bearing No. R14ZZ

Size	22.225x47.625x12.700 mm
Bore Diameter	22,225 mm
Outer Diameter	47,625 mm
Width	12,700 mm
d	22,225 mm
D	47,625 mm
B	12,700 mm
C	12,700 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Inch
Long Description	7/8" Bore; 1-7/8" Outside Diameter; 1/2" Outer Race



## Shandong Chik Bearing Co., Ltd.

	Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Interna
Other Features	Deep Groove   Miniature Bearing   Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Weight / LBS	0.159
Bore	0.875 Inch   22.217 Millimeter
Outside Diameter	1.875 Inch   47.625 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.5 Inch   12.7 Millimeter
bore diameter:	0.8750 in
precision rating:	Class 0
outside diameter:	1.8750 in
finish/coating:	Uncoated
overall width:	0.5000 in
bearing material:	High Carbon Chrome
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	0.5000 in
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	0.5000 in



## Shandong Chik Bearing Co., Ltd.

snap ring included:	Without Snap Ring
maximum rpm (grease):	16000 rpm
internal clearance:	CN
fillet radius:	0.0310 in
operating temperature range:	-40 to 250 ° F
maximum rpm:	18000 RPM
dynamic load capacity:	1740 lbf
series:	R
static load capacity:	1160 lbf
manufacturer product page:	<a href="#">Click here</a>